

20

EASY-POWER

STANDARD EQUIPMENT

The plus of EFFER

The benefits to the enduser

- Main boom raising angle up to 82°
One can make full use of the boom length to reach close to 8 m of height, a record in this class
- Excellent power-to-weight ratio
When fitting the crane on a 3,5 tons GWV truck, the remaining payload is still very good, even with a tipper
- Protecting guard at the controls stand (1)
A functional dashboard with an attractive design for an improved comfort
- Up to two hydraulic extensions
A record boom length allows to sweep the whole work-area
- Minimal mounting space behind cabin
One may fully use the body length without losing loading volume
- Turret and pins on bronze bushings
Longer life even by the most intensive works
- Single-stage extensions cylinders self-supported
Longer life of the gaskets on the cylinders pistons

		1S	2S
Max. hydraulic outreach	m	4,30	5,64
Max. lifting moment (+15°)	kgm kNm	1565 15,35	1486 14,57
Slewing arc	degrees rad		360 6,28
Slewing moment	kgm kNm		275 2,69
Working pressure	bar MPa		180 18
Recommended oil delivery	l/min dm3/sec		8 0,13
Oil tank capacity	l dm3		25 25
Weight of the standard crane (± 2%)	kg	330	355

AVAILABLE OPTIONS

The plus of EFFER

The benefits to the enduser

- Mechanical extensions
Longer reaches available without losing weight or lifting capacity
- Special paint colour (RAL Codes)
Get your vehicle with your own company livery

Technical updates may modify stated data

Dealer



EFFER Holding S.p.A.

Via C. Bonazzi 12/14 - 40013 Castel Maggiore (BO) Italy
tel. +39 051 4181211 - fax +39 051 701492
www.effer.it - e-mail: truckcranes@effer.it